
**Pacific Northwest
National Laboratory**

Operated by Battelle for the
U.S. Department of Energy

**Area Monitoring Dosimeter Program
For the Pacific Northwest National
Laboratory: Results for CY 2003**

S.R. Bivins
G.A. Stoetzel

June 2004



Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RL01830

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any of their employees, makes **any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.** Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or Battelle Memorial Institute. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PACIFIC NORTHWEST NATIONAL LABORATORY
operated by
BATTELLE
for the
UNITED STATES DEPARTMENT OF ENERGY
under Contract DE-AC06-76RL01830

Printed in the United States of America
Available to DOE and DOE contractors from the
Office of Scientific and Technical Information,
P.O. Box 62, Oak Ridge, TN 37831-0062;
ph: (865) 576-8401
fax: (865) 576-5728
email: reports@adonis.osti.gov

Available to the public from the National Technical Information Service,
U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161
ph: (800) 553-6847
fax: (703) 605-6900
Email: orders@ntis.fedworld.gov
online ordering: <http://www.ntis.gov/ordering.htm>



This document was printed on recycled paper.

(8/00)

**Area Monitoring Dosimeter Program for the
Pacific Northwest National Laboratory: Results
for CY 2003**

S.R. Bivins
G.A. Stoetzel

June 2004

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RL01830

Pacific Northwest National Laboratory
Richland, Washington 99352

Summary

In January 1993, Pacific Northwest National Laboratory (PNNL) established an area monitoring dosimeter program in accordance with Article 514 of the U.S. Department of Energy (DOE) Radiological Control Manual (RCM). The purpose of this program was to minimize the number of areas requiring issuance of personnel dosimeters and to demonstrate that doses outside Radiological Buffer Areas are negligible. In accordance with 10 CFR Part 835.402 (a) (1)-(4) and Article 511.1 of the PNNL Radiological Control Program Description, personnel dosimetry shall be provided to 1) radiological workers who are likely to receive at least 100 mrem annually and 2) declared pregnant workers, minors, and members of the public who are likely to receive at least 50 mrem annually. Program results for calendar years 1993-2002 confirmed that personnel dosimetry was not needed for individuals located in areas monitored by the program.

Area thermoluminescent dosimeters (TLDs) were placed at 124 locations in PNNL facilities during calendar year 2003. The TLDs were exchanged and analyzed quarterly. All routine area monitoring TLD results were less than 50 mrem annually after correcting for worker occupancy. The results support the conclusion that personnel dosimeters are not necessary for staff, declared pregnant workers, minors, or members of the public in these monitored areas.

Contents

Summary	iii
1.0 Introduction	1.1
2.0 Materials and Methods	2.1
2.1 Description of Area TLDs	2.1
2.1.1 Hanford Standard Dosimeter.....	2.1
2.1.2 Hanford Combination Neutron Dosimeter	2.2
2.2 Placement of Area TLDs	2.2
2.3 Frequency of Area TLD Exchange.....	2.3
2.4 Data Review	2.3
2.5 Quality Assurance and Quality Control.....	2.4
3.0 Results and Discussion	3.1
3.1 Area TLD Results (Deep Dose)	3.2
3.2 Area TLD Results (Deep + Neutron Dose)	3.3
4.0 Conclusions	4.1
5.0 References	5.1
Appendix A - Area TLD - Processing, Calibration, and Dose Assessment	A.1
Appendix B - Locations of Area Monitoring TLDs	B.1
Appendix C - Area Monitoring TLD Results for CY 2003	C.1

Tables

3.1	Summary of Area Monitoring TLD Results, CY 2003	3.1
3.2	Estimated Annual Dose to an Individual at Selected Locations, CY 2003	3.5
3.3	Comparison of Neutron Doses between Hanford Standard Dosimeters and Hanford Combination Neutron Dosimeter, CY 2001 - 2003.....	3.6

Figures

3.1	Deep Dose Trend Data, CY 2003	3.7
-----	-------------------------------------	-----

1.0 Introduction

The U.S. Department of Energy Standard on Radiological Control (DOE Standard) (DOE 1999), first issued as the DOE Radiological Control Manual (RCM) in 1992, provides guidelines to assist line managers in meeting their responsibilities for implementing occupational radiological control programs. Article 514 of the DOE Standard, included in the PNNL Radiological Control Program Description, discusses the establishment and maintenance of a comprehensive area monitoring dosimeter program to minimize the number of areas requiring issuance of personnel dosimeters and to demonstrate that doses outside of radiological areas are negligible. This program complies with 10 CFR Part 835.401(a)(3), 401(a)(6), 402(a)(3), 401(a)(4), and 1003(b). As discussed in Article 514 of the PNNL Radiological Control Program Description, area monitoring dosimeters should do the following:

- record and document radiation levels in routinely occupied areas adjacent to areas where radiation or operations with radiation exist (not applicable when the radiation arises solely from low-energy beta sources such as ^{14}C or ^3H)
- support dosimetry investigations where personnel express concern about their work environment and exposure to ionizing radiation
- supplement existing monitoring programs in Radiologically Controlled Areas and provide data in the event of an emergency.

In January 1993, Pacific Northwest National Laboratory (PNNL)⁽¹⁾ established an area monitoring thermoluminescent dosimeter (TLD) program in accordance with Article 514 of the RCM. The program was conducted as outlined by Bivins⁽²⁾ during calendar years (CY) 1993 and 1994. The program is now implemented according to RCP-5.1.04, "Area Monitoring TLD Program," issued in PNL-MA-266, *PNL Radiological Control Implementing Procedures*. Program results for previous years are found in Bivins and Stoetzel (1996a, 1996b, 1997, 1998, 1999, 2000, 2001, 2002, and 2003). Data from the program was also used to support the PNNL As Low As Reasonably Achievable (ALARA) program.

A description of the materials and methods used in collecting area monitoring TLD data and program results for CY 2003 are presented in this report. Neutron dose readings from the area TLDs are included in Section 3.0. Reporting of neutron dose data was initiated in the CY 1998 report (Bivins and Stoetzel 1999).

-
- (1) The Pacific Northwest National Laboratory is operated for the U.S. Department of Energy by Battelle under Contract DE-AC06-76RL01830. Battelle also owns and operates private facilities near the Hanford Site.
 - (2) Bivins, S. R. February 24, 1993. Letter Report to D.P. Higby entitled "Area Monitoring Dosimeter." Pacific Northwest National Laboratory, Richland, Washington.

2.0 Materials and Methods

This section provides information on the type of TLDs used in the program, how they were located in the field, and frequency of exchange. Derivation of the investigation level, which triggers an evaluation into the potential cause of a reading, is also provided.

2.1 Description of Area TLDs

The Hanford Standard Dosimeter and the Hanford Combination Neutron Dosimeter were used in this program during CY 2003. The Hanford Standard Dosimeter was used at all locations; in addition, the Hanford Combination Neutron Dosimeter was positioned at two locations to better quantify neutron doses.

A brief description of each type of dosimeter is presented below. Appendix A provides a description of TLD processing, calibration, and the dose algorithm used in determining doses.

2.1.1 Hanford Standard Dosimeter

The Hanford Standard Dosimeter is accredited by the DOE Laboratory Accreditation Program (DOELAP) and is known commercially as a Harshaw 8825 dosimeter. The dosimeter contains TLD-700 chips in positions one, two, and three and a TLD-600 chip in position four. The TLD-600 chip is neutron-sensitive. The chips have thicknesses of 0.38 mm (100 mg/cm²) in positions one, two, and four, and 0.15 mm (40 mg/cm²) in position three. The TLD holder is constructed of black plastics with the following filtration:

1. position one - 242 mg/cm² acrylonitrilebutadienestyrene (ABS) plastic and 91 mg/cm² copper
2. position two - 1000 mg/cm² ABS plastic and Teflon[®]
3. position three - 8 mg/cm² Teflon[®] and 9 mg/cm² mylar
4. position four - 240 mg/cm² ABS plastic and 463 mg/cm² tin.

These dosimeters were read for shallow dose, deep dose, neutron dose, and eye dose. Only deep dose and neutron dose readings are discussed in this report.

[®] Teflon is a registered trademark of E. I. Du Pont de Nemours Co., Inc., Wilmington, Delaware.

2.1.2 Hanford Combination Neutron Dosimeter

The Hanford Combination Neutron Dosimeter consists of three components: 1) a beta-photon TLD, 2) an albedo neutron TLD, and 3) two CR-39 track-etch dosimeter foils. Instead of CR-39 track-etch dosimeter foils, the albedo neutron TLD is currently used to assess neutron dose. The beta-photon TLD is a Harshaw 8825 dosimeter. The albedo neutron TLD is a Harshaw 8816 dosimeter, which contains three TLD-600 phosphors and one TLD-700 phosphor. This albedo TLD has the following filter configurations:

- TLD-700 #1 (tin filters on the front and back)
- TLD-600 #2 (cadmium filter on front and tin filter on back)
- TLD-600 #3 (tin filter on front and cadmium filter on back)
- TLD-600 #4 (tin filters on front and back).

These dosimeters were read for shallow dose, deep dose, neutron dose, and eye dose. Only deep dose and neutron dose readings are discussed in this report.

2.2 Placement of Area TLDs

Area TLDs were placed in the following PNNL facilities (DOE-owned, DOE-leased, and Battelle private):

- all 300 Area PNNL facilities where staff worked at least eight hours per month
- all PNNL facilities where staff conducted radiological work (i.e., had a current Radiological Work Permit)
- all PNNL facilities located within 15 m (~50 ft) of another facility (including those of other Hanford Site contractors) containing a radiological area (indoors or outdoors).

TLDs positioned as such are referred to as “routine” area TLDs in this report. Area TLDs were also positioned in facilities as approved by the Radiological Control organization for special situations such as ALARA evaluations. In this report, these are referred to as “special” area TLDs.

A list of routine area TLD locations is included as Appendix B. There were no special area TLD locations during CY 2003. The number of area TLDs in each facility was determined according to the following criteria:

- at least one area TLD per facility
- one additional area TLD for every 25 staff members in facilities requiring area TLDs but not containing a Radiologically Controlled Area or a radiological area
- one additional area TLD for every 15 staff members in facilities requiring area TLDs and containing a Radiologically Controlled Area or a radiological area.

Hanford Combination Neutron Dosimeters were positioned as area TLDs at the following two locations to better quantify neutron doses:

- 325 Building, Room 101
- 326 Building, Room 28B on the second floor.

Additional area TLDs were positioned as determined by the Radiological Control organization.

Each Hanford Standard Dosimeter used as an area TLD was oriented per guidance in PNL-MA-842, *Hanford External Dosimetry Technical Basis Manual*. If the potential source of exposure was from within the facility, the area TLD was placed on the wall opposite the potential source. If the potential source of exposure was located outside the facility, the area TLD was placed on the inside surface of the exterior wall with the Mylar window facing away from the wall. The TLDs were placed 1 to 2 m (3 to 6 ft) from the floor, depending on whether staff in the area would be standing or seated.

Each Hanford Combination Neutron Dosimeter used as an area TLD was placed on the front-face of a 5-gallon carboy filled with water. The neutron portion of the dosimeter was at least 7.5 cm (3 in) from any edge of the carboy. The physical size and weight of the 5-gallon carboy limited the locations where these dosimeters could be positioned.

Each area TLD was identified with an attached bar code label containing a facility ID (e.g., 337, LOC. 5) and a TLD identification number beginning with the letter “A” to denote an area TLD followed by a four-digit number (e.g., A3014).

2.3 Frequency of Area TLD Exchange

All area TLDs were scheduled to be exchanged and analyzed quarterly. The area monitoring TLD procedure allows facility managers to request a special exchange for any TLD in their facilities. The Safety & Health Manager may also request a special exchange for area TLDs in any facility. Any area TLD changed out was immediately replaced with another area TLD unless the area TLD location was being discontinued.

2.4 Data Review

Any area TLD results greater than or equal to 40 mrem in a quarter were investigated. This action level was established to ensure that an individual would not likely receive more than 50 mrem annually (the trigger level for requiring personnel dosimetry for declared pregnant workers, minors, and members of the public). The investigation level of 40 mrem per quarter was derived by dividing the 50 mrem annual limit by four and adjusting for worker occupancy.

The area TLDs were exposed for approximately 8760 h annually; individual occupancy was assumed to be 2000 h (8 h/d, 5 d/wk, and 50 wk/yr). Therefore, the occupancy-corrected quarterly limit is as follows:

$$\text{Quarterly limit} = (50 \text{ mrem}/4)(8760 \text{ h}/2000 \text{ h}) = 55 \text{ mrem}$$

The calculated 55-mrem quarterly limit was reduced to 40 mrem to allow for such factors as processing time, processing errors, the potential for individuals to be present more than 2000 h annually, and the potential for maximum exposure rates occurring during occupancy hours.

2.5 Quality Assurance and Quality Control

The Hanford External Dosimetry Project (HEDP) performed the measurements of the area TLDs. The HEDP laboratory is DOELAP accredited. Quality assurance and quality control programs are conducted in accordance with PNL-MA-859, *Hanford External Dosimetry Project Quality Manual*.

3.0 Results and Discussion

A summary of the deep dose area monitoring TLD results for CY 2003 is provided in Table 3.1. Quarterly area monitoring TLD results are grouped into one of three dose ranges (i.e., ≤ 10 mrem; > 10 mrem but < 40 mrem; ≥ 40 mrem). In four locations, deep dose results exceeded the quarterly investigation level of 40 mrem; however, none of these locations had potential personnel exposures of 50 mrem after considering worker occupancy. The results support the conclusion that personnel dosimeters are not necessary for staff in the areas monitored by the area TLDs. A detailed discussion of these four area monitoring TLD locations is found in Section 3.1.

Table 3.1 Summary of Area Monitoring TLD Results, CY 2003^a

Parameter	Quantity
Number of area TLD locations	124
Total number of area TLDs analyzed in CY 2003	463 ^b
Quarterly area TLD results by deep dose range:	
• ≤ 10 mrem	422
• > 10 mrem but < 40 mrem	29
• ≥ 40 mrem	12

- This table provides data for routine area TLDs. No special area TLDs were located in the field during CY 2003.
- The total number of area TLDs analyzed does not equal 496 (i.e., four times the number of area TLD locations) because locations were started and terminated at various times throughout the year and several area TLDs were lost.

The neutron dose readings from the Hanford Standard Dosimeters typically over-estimate neutron dose since they are calibrated to an unmoderated neutron source, and neutron fields in PNNL facilities are moderated by intervening shielding and building materials. To better quantify neutron doses, Hanford Combination Neutron Dosimeters were positioned at two locations in CY 2003. Comparison of neutron results between the Hanford Standard Dosimeter and Hanford Combination Neutron Dosimeter are presented in Section 3.2, along with a discussion of three locations where the combined deep and neutron dose results for CY 2003 exceeded the quarterly investigation level of 40 mrem.

Individual area monitoring TLD results for each quarter, as well as annual totals, are presented in Appendix C. The results in Appendix C are not corrected for worker occupancy. Assuming workers to be present 2000 h/yr, results should be multiplied by 0.23 to correct for worker occupancy.

3.1 Area TLD Results (Deep Dose)

Quarterly “deep dose” area monitoring TLD results for facilities located outside the 300 Area (622R, 747A, 747A Trl, 2400 Stevens, APEL, BRSW, EMSL, ESB, LSL-II, PSL, RTL, and Sigma V) were ≤ 10 mrem except for one EMSL quarterly result which was 11 mrem. The four locations with quarterly deep dose results ≥ 40 mrem “investigation level” were located in the 325 Building. Figure 3.1 shows the trend of annual deep dose results at the four locations since the PNNL program was initiated in 1993. Table 3.2 provides estimated annual doses to an individual at the locations for CY 2003 considering occupancy. Estimated doses were below the 50 mrem annual dose, which requires personnel dosimetry for a declared pregnant worker, a minor, or a member of the public. Detailed reviews of each location are summarized below.

- TLD ID# A3062 (325, Loc. 2) was located in Room 5 of the mezzanine of the 325 Building on the north wall about chest height. This location was initiated in 1993. The increase in dose since 1997 (see Figure 3.1) was due to increased waste handling and storage activities in the basement of the 325 Building. Waste is frequently stored along the south wall of the basement just below Room 5. Routine surveys taken in the mezzanine annually showed that dose rates are less than the 50 μ rem/h level requiring posting as a Radiological Buffer Area. Accounting for occupancy, an individual could have received approximately 42 mrem during CY 2003 (see Table 3.2).
- TLD ID# A3175 (325, Loc. 5) was located in the lunchroom of the east equipment room on the second floor of the 325 Building. This location was initiated in the second quarter of CY 1997. The annual deep dose result at this location has increased since 1999 (see Figure 3.1). The increase in deep dose results over the past four years was attributed to storage of additional radioactive material in Room 528 located below this area. Accounting for occupancy, an individual could have received approximately 25 mrem during CY 2003 (see Table 3.2).
- TLD ID# A3176 (325, Loc. 6) was located in the copy room in the second floor office area (Room 915) of the 325 Building during the first quarter of CY 2003 and then moved to Room 916 for the remainder of the year. This location was initiated in 1998. The annual deep dose result for CY 2003 decreased by a factor of four over the results from CY 2002 (see Figure 3.1). This decrease was attributed to the completion of sample preparation work on high-activity filters located in room 700 and also to the movement of the area TLD to Room 916. The CY 2003 result of 175 mrem was similar to results from CY 1999-2001. Accounting for occupancy, an individual could have received approximately 10 mrem during CY 2003 (see Table 3.2).
- TLD ID# A3196 (325, Loc. 7) was located on the wall between Room 115 and 116 on the first floor of the 325 Building. This location was started in the second quarter of CY 1999. The total deep dose for CY 2003 was 386 mrem about 10% lower than previous years (see Figure 3.1). Accounting for occupancy, an individual could have received approximately 24 mrem during CY 2003 (see Table 3.2).

3.2 Routine Area TLD Results (Deep + Neutron Dose)

Neutron dose results for the Hanford Standard Dosimeter are based on a calibration on a phantom to unmoderated neutrons from bare ^{252}Cf . The neutrons typically reaching an area TLD location will be moderated by intervening shielding and building material; therefore, the dosimeter would be more appropriately calibrated in air to a ^{252}Cf source moderated by a 30-cm-diameter sphere of D_2O . This calibration showed that the neutron doses reported in Appendix C should be divided by a factor of 2.66 to obtain more accurate results. Field measurements made with a BF_3 detector showed that the correction factor of 2.66 could also be conservatively used to correct neutron readings for a location in the 331 Building. To better define neutron doses from the Hanford Standard Dosimeter, over the past several years Hanford Combination Neutron Dosimeters have been placed at selected locations, which had elevated neutron readings on the Hanford Standard Dosimeters. During CY 2003, Hanford Combination Neutron Dosimeters were located at 1) 326, Loc. 9 (Rm 28B), and 2) 325, Loc. 12 (Room 101). Several locations (i.e., 325, Loc. 5 and 325, Loc. 7) were discontinued as enough information had been gathered on ratios of neutron dose from the Hanford Standard Dosimeter and the Hanford Combination Neutron Dosimeter. Comparisons of neutron dose readings are found in Table 3.3. The results showed the Hanford Standard Dosimeter to over-respond by a factor of up to 9.3. The Hanford Standard Dosimeters in the 325 Building over-responded by an average of 7.6 compared to an average of only 1.4 in the 326 Building. The likely reason for this difference is that the source of the neutron exposure in the 326 Building is located closer to the area dosimeters with less intervening shielding compared to the neutron exposures in the 325 Building. Therefore, the 326 Building exposure configuration more closely aligns to the neutron calibration method for the Hanford Standard Dosimeter (i.e., calibration on a phantom to unmoderated neutron from bare ^{252}Cf).

Three area TLD locations had quarterly readings exceeding the 40 mrem “investigation level” when totaling the deep dose and neutron dose reading. A discussion of the three area TLD locations is presented below:

- TLD ID# A3197 (325, Loc. 8) was located on the first floor of the 325 Building between Room 101 and 102. This location was initiated during the second quarter of CY 1999. Quarterly deep dose results for CY 2003 ranged from 16 to 22 mrem (79 mrem total for the year) which is similar to the quarterly results for previous years. Quarterly neutron doses ranged from 46 to 52 mrem (202 mrem total) for CY 2003, which is similar to the readings for the third quarter of CY 2000. Using the 2.66 correction factor, the annual neutron dose for CY 2003 is estimated to be 76 mrem. Doses are likely due to radioactive materials found in Room 22 of the basement below this hallway. Accounting for occupancy, an individual could have received approximately 9 mrem during CY 2003 (see Table 3.2).

- TLD ID #A3230 (325, Loc. 11) and A3231 (325, Loc. 12) were located in Room 101 of the 325 Building. These dosimeters were added during the third quarter of CY 2003 to better define neutron doses in the area. TLD #A3230 was a Hanford Standard Dosimeter and TLD #A3231 was a Hanford Combination Neutron Dosimeter. The combined deep dose result for the third and fourth quarter was 36 mrem which projects to be 72 mrem for the year. Neutron results for this location are found in Table 3.3. Quarterly neutron dose results from the Hanford Standard Dosimeter were an average of approximately 8 times greater than the neutron dose results from the Hanford Combination Neutron Dosimeter at this location. Combined neutron dose results from the Hanford Combination Neutron Dosimeter for the third and fourth quarter was 28 mrem which projects to be 56 mrem for the year. Accounting for occupancy, an individual could have received ~30 mrem at this location during CY 2003 (see Table 3.2).
- TLD ID# A3218 (326, Loc. 9) and A3222 (326, Loc. 10) were located on the second floor of the 326 Building in Room 28B under the window on the south wall. TLD A3218 (Hanford Standard Dosimeter) was initiated during the fourth quarter of CY 1999 and TLD A3222 (Hanford Combination Neutron Dosimeter) was initiated during the first quarter of CY 2002. The deep dose readings were insignificant (<10 mrem/quarter) which is similar to past years. Neutron results for this location are found in Table 3.3. For CY 2003, quarterly neutron dose results from Hanford Standard Dosimeter were up to 1.3 greater than dose results from the Hanford Combination Neutron Dosimeter at this location. Neutron doses for three of the four quarters exceeded the 40 mrem screening limit. The source of the neutron activity was neutron source storage in room 9A. When these sources are removed from their storage locations during projects, personnel are evacuated from the areas immediately above Room 9A. Accounting for occupancy, an individual could have received approximately 13 mrem during CY 2003 (see Table 3.2).

Table 3.2 Estimated Annual Dose to an Individual at Selected Locations, CY 2003


Location	Dosimeter Number	Annual Area TLD Reading (mrem)	Estimated Dose to Individual Assuming Full-Time Occupancy (mrem) ^a	Occupancy Factor	Estimated Annual Dose to Individual After Occupancy Corrections (mrem)
325, Loc. 2 (Rm 5)	A3062	183 ^b	42	1	42
325, Loc. 5 (east equip rm)	A3175	434 ^c	100	¼	25
325, Loc. 6 (2 nd floor, copy room)	A3176	175	40	¼	10
325, Loc. 7 (Rm 115/116)	A3196	413 ^d	95	¼	24
325, Loc. 8 (hallway outside of Rm 101/102)	A3197	155 ^e	36	¼	9
325, Loc. 11 and Loc. 12 (Rm 101)	A3230, A3231	128 ^f	29	1	29
326, Loc. 9 and Loc. 10 (Rm 28B)	A3218, A3222	223 ^g	51	¼	13

- a. Full-time occupancy assumes 2000 hours/y; therefore, need to multiply value in previous column by 0.23.
- b. Dose was the sum of the deep dose reading for CY 2003 (176 mrem) and the neutron dose divided by 2.66 (18 mrem/2.66 = 7 mrem).
- c. This dose represents the sum of the annual deep dose (426 mrem) and the neutron dose divided by 2.66 (20 mrem/2.66 = 8 mrem).
- d. This dose represents the sum of the annual deep dose (386 mrem) and the neutron dose divided by 2.66 (71 mrem/2.66 = 27 mrem).
- e. Dose was the sum of the deep dose reading (79 mrem) and the neutron dose divided by 2.66 (202 mrem/2.66 = 76 mrem).
- f. This dose represents the sum of the deep dose (36 mrem) and the neutron dose (28 mrem) times two to project for a full year.
- g. This dose represents the sum of the annual deep dose (32 mrem) and neutron dose (191 mrem). The neutron dose reading was taken from the Hanford Combination Neutron Dosimeter (A3222).

Table 3.3 Comparison of Neutron Doses between Hanford Standard Dosimeter and Hanford Combination Neutron Dosimeter, CY 2001 -2003

Quarter	Neutron Dose (mrem)								
	325, Loc. 5 (East Equipment Rm)			325, Loc. 12 (Rm 101)			326, Loc. 9 (Rm 28B)		
	Std (A3175)	Combo (A3225)	Ratio (Std/Combo)	Std (A3230)	Combo (A3231)	Ratio (Std/combo)	Std (A3218)	Combo (A3222)	Ratio (Std/combo)
2001-1	-	-	-	-	-	-	82	23	3.6
2001-2	-	-	-	-	-	-	34	9	3.8
2001-3	80	14	5.7	-	-	-	68	44	1.6
2001-4	75	11	6.8	-	-	-	61	51	1.2
2002-1	64	8	8.0	-	-	-	56	50	1.1
2002-2	55	6	9.2	-	-	-	49	40	1.2
2002-3	-	-	-	-	-	-	56	42	1.3
2002-4	-	-	-	-	-	-	53	49	1.1
2003-1	-	-	-	-	-	-	46	38	1.2
2003-2	-	-	-	-	-	-	63	47	1.3
2003-3	-	-	-	121	13	9.3	68	55	1.2
2003-4	-	-	-	109	15	7.3	51	51	1.0
Total	274	39	7.0	230	28	8.2	687	499	1.4

Figure 3.1 CY 2003 Deep Dose Trend Data



4.0 Conclusions

The area monitoring TLD program for CY 2003 was a useful tool in determining exposure trends in work areas located outside radiological areas. All routine area monitoring TLD results were less than 50 mrem annually after correcting for worker occupancy. The results support the conclusion that personnel dosimeters are not required for staff in these monitored areas.

5.0 References

Bivins SR, and GA Stoetzel. 1996a. *Area Monitoring Dosimeter Program for the Pacific Northwest National Laboratory: Results for CY 1993 and CY 1994*. PNNL-11088, Pacific Northwest National Laboratory, Richland, Washington.

Bivins SR, and GA Stoetzel. 1996b. *Area Monitoring Dosimeter Program for the Pacific Northwest National Laboratory: Results for CY 1995*. PNNL-11185, Pacific Northwest National Laboratory, Richland, Washington.

Bivins SR, and GA Stoetzel. 1997. *Area Monitoring Dosimeter Program for the Pacific Northwest National Laboratory: Results for CY 1996*. PNNL-11594, Pacific Northwest National Laboratory, Richland, Washington.

Bivins SR, and GA Stoetzel. 1998. *Area Monitoring Dosimeter Program for the Pacific Northwest National Laboratory: Results for CY 1997*. PNNL-11924, Pacific Northwest National Laboratory, Richland, Washington.

Bivins SR, and GA Stoetzel. 1999. *Area Monitoring Dosimeter Program for the Pacific Northwest National Laboratory: Results for CY 1998*. PNNL-12215, Pacific Northwest National Laboratory, Richland, Washington.

Bivins SR, and GA Stoetzel. 2000. *Area Monitoring Dosimeter Program for the Pacific Northwest National Laboratory: Results for CY 1999*. PNNL-13322, Pacific Northwest National Laboratory, Richland, Washington.

Bivins SR, and GA Stoetzel. 2001. *Area Monitoring Dosimeter Program for the Pacific Northwest National Laboratory: Results for CY 2000*. PNNL-13604, Pacific Northwest National Laboratory, Richland, Washington.

Bivins SR, and GA Stoetzel. 2002. *Area Monitoring Dosimeter Program for the Pacific Northwest National Laboratory: Results for CY 2001*. PNNL-13937, Pacific Northwest National Laboratory, Richland, Washington.

Bivins SR, and GA Stoetzel. 2003. *Area Monitoring Dosimeter Program for the Pacific Northwest National Laboratory: Results for CY 2002*. PNNL-14323, Pacific Northwest National Laboratory, Richland, Washington.

National Council on Radiation Protection and Measurements (NCRP). 1976. *Structural Shielding Design and Evaluation for Medical Use of X Rays and Gamma Rays of Energies Up to 10 MeV*. NCRP Report No. 49, NCRP, Washington, DC 20014.

PNL-MA-266, *PNL Radiological Control Implementing Procedures*.

PNL-MA-842, *Hanford External Dosimetry Project Technical Basis Manual*.

PNL-MA-859, *Hanford External Dosimetry Project Quality Manual*.

PNNL Radiological Control Program Description, November 1999.

U.S. Department of Energy (DOE). 1994. *Radiological Control Manual*. DOE/EH-0256T, Rev. 1, Washington, D.C.

U.S. Department of Energy (DOE). 1999. *DOE Standard – Radiological Control*. DOE-STD-1098-99. July 1999. Washington, D.C.

Appendix A

Area TLD - Processing, Calibration, and Dose Assessment

Appendix A

Area TLD - Processing, Calibration, and Dose Assessment

A.1 Processing

Harshaw 8800 series automated reader systems were used to process the area thermoluminescent dosimeters (TLDs) (i.e., Hanford Standard Dosimeter and Hanford Combination Neutron Dosimeter). Automated processing steps included the following:

- **Pre-issue reader annealings:** each dosimeter card is processed through the automated reader systems to remove any remaining residual signal from past occupational exposure or environmental background radiation. Each dosimeter card is annealed at 80°C for 16 h before being issued.
- **Reader processing:** the reader heats all chips simultaneously at a rate of 25°C/s until a maximum temperature of 300°C is obtained.
- **Glow-curve recording:** the glow curve of all dosimeters is recorded and stored for a period of approximately 2 years.

A.2 Calibration

Area TLDs were calibrated using sources traceable to the National Institute of Standards and Technology (NIST). The primary calibration was the deep dose from an on-phantom ¹³⁷Cs exposure.

A.3 Dose Assessment

The contribution to the area TLD from naturally occurring environmental radiation was determined using the following equation:

$$E_i = G_i (FD - BD)$$

where E_i = estimated environmental background for chip i (⁶⁰Co mR-equivalent)
 G_i = background growth rate (mR/d)
FD = field cycle days (days between previous and current processing date)
BD = blank days (mean days between previous and current processing for blank cards).

The adjusted chip readings are calculated using the following equation:

$$D_i = \frac{X_i B_i E_i}{(RRF_i * F_i)}$$

where D_i = adjusted chip reading for chip i (^{137}C rem-equivalent)
 X_i = calibrated chip reading for chip i (^{60}Co mR-equivalent)
 B_i = mean calibrated chip i reading from blank cards (^{60}Co mR-equivalent)
 E_i = estimated environmental background for chip i (^{60}Co mR-equivalent)
 RRF_i = ^{137}Cs relative response factor (RRF) for chip i (mR/rem)
 F_i = fade factor for chip i.

Area TLD readings were provided for shallow dose, deep dose, neutron dose, and eye dose. Only deep dose and neutron results are included for discussion in this report.

A.4 Dose Algorithm

Dose algorithms for the Hanford Standard Dosimeter and Hanford Combination Neutron Dosimeter are found in Section 8 of PNL-MA-568.

A.5 Quality Control Program

Quality assurance and quality control programs are conducted in accordance with Section 5 of PNL-MA-859, *Hanford External Dosimetry Project Quality Manual*.

Appendix B

Locations of Area Monitoring TLDs

Appendix B

Locations of Area Monitoring TLDs

BLDG	TLD ID #	Location ID #	Description of Location
		Routine TLDs	
305-B	A3001	LOC. 1	South wall of Room 2 near vending machine
306-W	A3034	LOC. 1	Main entrance on first bulletin board
306-W	A3035	LOC. 2	Second floor lunchroom
306-W	A3036	LOC. 3	First floor - Room 131
318	A3040	LOC. 2	Main corridor of second floor across from Room 202
318	A3192	LOC. 4	First floor - main corridor outside Room 121
318	A3193	LOC. 5	Bulletin board across from Room 1128 (facing north)
318	A3194	LOC. 6	Room 169 (copy room) - north wall
318	A3022	TRL. 4	Bulletin board on the north wall (main entrance)
320	A3042	LOC. 1	Lobby
320	A3043	LOC. 2	Basement on bulletin board outside of Room 5 on east wall
323	A3195	LOC. 1	Lunchroom on south wall facing hot cell area
325	A3061	LOC. 1	Main lobby near north door
325	A3062	LOC. 2	Mezzanine, Room 5, north wall (chest height)
325	A3063	LOC. 3	Second floor - outside of Room 944
325	A3174	LOC. 4	Lunchroom (second floor)
325	A3175	LOC. 5	East equipment room (second floor, lunch area)
325	A3176	LOC. 6	Room 915 – 1 st quarter; Room 916 – remainder of year
325	A3196	LOC. 7	First floor hallway between Rooms 115 and 116
325	A3197	LOC. 8	First floor hallway between Rooms 101 and 102
325	A3198	LOC. 9	Mezzanine, Room 76
325	A3199	LOC. 10	Mezzanine, Room 17
325	A3230	LOC. 11	Room 101 (location in room)
325	A3231	LOC. 12	Room 101 (location in room) (Hanford Combination Neutron Dosimeter)
326	A3064	LOC. 1	First floor - bulletin board in copy area (Room 15)
326	A3065	LOC. 2	First floor - in front of exit door to basement
326	A3066	LOC. 3	First floor - in corridor across from Room 48-B
326	A3067	LOC. 4	Second floor - lunchroom bulletin board
326	A3068	LOC. 5	Second floor - corridor near Room 40-C
326	A3157	LOC. 6	Basement - Room 14A bulletin board

BLDG	TLD ID #	Location ID #	Description of Location
326	A3178	LOC. 7	Room 37B (second floor, east wall)
326	A3200	LOC. 8	Second floor on bulletin board opposite Room 30-C
326	A3218	LOC. 9	Second floor, Room 28B, under window on south wall
326	A3222	LOC. 10	Second floor, Room 28B, under window on south wall (Hanford Combination Neutron Dosimeter)
326	A3229	LOC. 11	Room 17B/19B
329	A3071	LOC. 1	Lunchroom
329	A3072	LOC. 2	Room 115 - east wall
329	A3074	LOC. 4	North-south hallway (Room 2)
329	A3075	LOC. 5	North-south hallway (Room 6-C)
329	A3173	LOC. 8	Room 129 (above sink)
331	A3044	LOC. 1	First floor - mail room
331	A3045	LOC. 2	Second floor hallway on bulletin board outside of Room 22
331	A3046	LOC. 3	Third floor - Room 45
331	A3201	LOC. 4	First floor on bulletin board (east wall of Room 166B)
331	A3202	LOC. 5	First floor on bulletin board (east wall of Room 113A)
331	A3203	LOC. 6	First floor on bulletin board (northeast wall of Room 164)
331	A3204	LOC. 7	First floor, Room 164 on northeast wall
331	A3205	LOC. 8	First floor - outside of Room 110
331	A3206	LOC. 9	Second floor in corridor opposite of Room 30
331	A3232	LOC. 10	Room 149
331	A3237	LOC. 11	Room 148 by RGD control panel
331C	A3207	LOC. 1	North wall by entrance door
331D	A3208	LOC. 1	North wall by entrance door
331H	A3209	LOC. 1	Bulletin board by airlock area
336-1	A3073	LOC. 1	Bulletin board in Room 5 on east wall at entrance to Room 6
337	A3080	LOC. 1	First floor south - west wall of Room 1114
337	A3081	LOC. 2	First floor north - east wall of Room 1225
337	A3082	LOC. 3	Second floor south - west wall of Room 2112
337	A3083	LOC. 4	Second floor north - north wall of Room 2213
337	A3084	LOC. 5	Third floor south - Room 3124
337	A3085	LOC. 6	Third floor north - Mt. Rainier Room
338	A3177	LOC. 1	Conference Room/lunchroom (Room 24) - west wall
350	A3004	LOC. 1	Bulletin board in Room 137
350	A3005	LOC. 2	Bulletin board between Rooms 158 and 175
622-R	A3086	LOC. 1	Room 110 by red phone
622-R	A3087	LOC. 2	Exit sign in front of men's room
747-A	A3088	LOC. 1	Bulletin board on west wall by scale
747-A	A3089	TRL.1, LOC. 1	Bulletin board by south door

BLDG	TLD ID #	Location ID #	Description of Location
2400	A3113	LOC. 1	Secretary's desk located in main entrance
2400	A3114	LOC. 2	Bulletin board in entry way to Room 1414
2400	A3115	LOC. 3	High-bay bulletin board in entry to Lab 1445
2400	A3116	LOC. 4	Second floor on bulletin board outside of Room 2428
3720	A3047	LOC. 1	North and south corridor across from Room 221
3720	A3048	LOC. 2	Bulletin board in lunchroom (Room 401), north wall
3730	A3049	LOC. 1	Desk area near computers
3760	A3009	LOC. 1	Lobby
3760	A3010	LOC. 2	Second floor Room 215 (SE cubicle)
APEL	A3217	LOC. 1	Room 102 on north wall by radiation generating device
APEL	A3228	LOC. 2	Room 80
BRSW	A3227	LOC. 1	Room 1 (receiving area above desk on fence)
EMSL	A3093	LOC. 1	Accelerator Room (north wall)
EMSL	A3094	LOC. 2	Accelerator Room (east wall)
EMSL	A3095	LOC. 3	Accelerator Room (south wall enclosure)
EMSL	A3096	LOC. 4	Accelerator Room (south wall)
EMSL	A3097	LOC. 5	Accelerator Room (west wall)
EMSL	A3098	LOC. 6	Accelerator Room (control console)
EMSL	A3211	LOC. 7	Room 1422 on south wall by phone
EMSL	A3212	LOC. 8	Room 1330 on south wall
EMSL	A3213	LOC. 9	Room 1330 on east wall under cabinet
EMSL	A3214	LOC. 10	Room 1330 on southwest wall
EMSL	A3219	LOC. 11	Room 1330, x-ray machine
EMSL	A3220	LOC. 12	Room 1422, x-ray machine
EMSL	A3223	LOC. 13	Room 1330 on north wall
EMSL	A3224	LOC. 14	Room 1330 on northeast wall
EMSL	A3235	LOC. 15	Room 1544 on north wall
EMSL	A3236	LOC. 16	Room 1544 northwest corner of room
ESB	A3092	LOC. 2	Entry way to Room 31
LSL-II	A3167	LOC. 1	Lunchroom
LSL-II	A3168	LOC. 2	Corridor outside of Lab 1404
LSL-II	A3169	LOC. 3	Lab 1508
LSL-II	A3170	LOC. 4	Lab 1419
LSL-II	A3171	LOC. 5	Office 1224
LSL-II	A3172	LOC. 6	Lab 1336
PSL	A3099	LOC. 1	Lab 1611
PSL	A3100	LOC. 2	Bulletin board in Lab 1504
PSL	A3101	LOC. 3	East entrance on secretary's desk
PSL	A3102	LOC. 4	Bulletin board in Lab 1304

BLDG	TLD ID #	Location ID #	Description of Location
PSL	A3103	LOC. 5	Corridor outside of Lab 315
PSL	A3210	LOC. 6	Room 1308 on west wall under cabinet
PSL	A3233	LOC. 7	Rm 1304
PSL	A3238	LOC. 8	Rm 429, southwest wall by RGD
PSL	A3234	LOC 9	Rm 415
RTL	A3105	LOC. 1	Lab 428
RTL	A3106	LOC. 2	Lab 328
RTL	A3107	LOC. 3	Lab 218
RTL	A3108	LOC. 4	Outside Room 127 Secretary office
RTL	A3109	LOC. 5	Canteen above fire extinguisher
RTL	A3110	LOC. 6	Bulletin board in Room 21-A
Sigma V	A3186	LOC. 1	Room 1519 - west wall
Sigma V	A3187	LOC. 2	Room 1519 - south wall
Sigma V	A3188	LOC. 3	Room 1519 - north wall
Sigma V	A3189	LOC. 4	Room 1227 - north wall
Sigma V	A3190	LOC. 5	Room 1523 - west wall
Sigma V	A3191	LOC. 6	Room 1519 - ceiling

Appendix C

Area Monitoring TLD Results for CY 2003

Appendix C

Area Monitoring TLD Results for CY 2003^(a)

TLD Location	TLD ID#	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)
		1st Quarter	2nd Quarter	3rd Quarter	4th Quarter	Annual
305B LOC. 1	A3001	1	0	3	0	4
306W LOC. 1	A3034	1	2	3	2	8
306W LOC. 2	A3035	4	4	5	4	17
306W LOC. 3	A3036	5	4	4	2	15
318 LOC. 2	A3040	4	3	4	2	13
318 LOC. 4	A3192	0	0	1	0	1
318 LOC. 5	A3193	0	0	0	0	0
318 LOC. 6	A3194	4	2	1	3	10
318 TRL. 4	A3022	0	2	0	0	2
320 LOC. 1	A3042	0	0	0	0	0
320 LOC. 2	A3043	5	5	4	6	20
323 LOC. 1	A3195	5	3	1	3	12
325 LOC. 1	A3061	0	0	0	0	0
325 LOC. 2	A3062	44	39 (8) ^e	49	44 (10) ^e	176 (18) ^e
325 LOC. 3	A3063	15	17 (10) ^e	27 (9) ^e	25 (8) ^e	84 (27) ^e
325 LOC. 4	A3174	0	0	1	0	1
325 LOC. 5	A3175	112	99	106 (20) ^e	109	426 (20) ^e
325 LOC. 6	A3176	82	37	27	29	175
325 LOC. 7	A3196	81	105 (29) ^e	102 (21) ^e	98 (21) ^e	386 (71) ^e
325 LOC. 8	A3197	20 (52) ^e	21 (52) ^e	22 (46) ^e	16 (52) ^e	79 (202) ^e

Area Monitoring TLD Results for CY 2003^(a) (continued)

TLD Location	TLD ID#	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)
		1st Quarter	2nd Quarter	3rd Quarter	4th Quarter	Annual
325 LOC. 9	A3198	11	10	8	9	38
325 LOC. 10	A3199	8	12	10	10	40
325 LOC. 11	A3230	(c)	(c)	18 (121) ^e	16 (109) ^e	34 (230) ^e
325 LOC. 12	A3231 (Combo)	(c)	(c)	19 (13) ^f	17 (15) ^f	36 (28) ^f
326 LOC. 1	A3064	2	1	0	1	4
326 LOC. 2	A3065	1 (20) ^e	1 (27) ^e	3 (21) ^e	1 (27) ^e	6 (95) ^e
326 LOC. 3	A3066	0	0	1	1	2
326 LOC. 4	A3067	0	0	0	0	0
326 LOC. 5	A3068	1	0	0	0	1
326 LOC. 6	A3157	9	2	6	10	33
326 LOC. 7	A3178	18	2	1	2	23
326 LOC. 8	A3200	0	0	0	0	0
326 LOC. 9	A3218	4 (46) ^e	9 (63) ^e	4 (68) ^e	3 (51) ^e	20 (228) ^e
326 LOC. 10	A3222 (Combo)	8 (38) ^f	9 (47) ^f	8 (55) ^f	7 (51) ^f	32 (191) ^f
326 LOC. 11	A3229	0	1	(b)	2	3
329 LOC. 1	A3071	0	0	0	0	0
329 LOC. 2	A3072	3	0	0	0 (9) ^e	3 (9) ^e
329 LOC. 4	A3074	0	0	0	0	0
329 LOC. 5	A3075	1 (18) ^e	3	5	1	10 (18) ^e
329 LOC. 8	A3173	11	16	16	8	51
331 LOC. 1	A3044	1	0	1	0	2
331 LOC. 2	A3045	3	2	2	1 (11) ^e	8 (11) ^e
331 LOC. 3	A3046	3	3	5	1	12
331 LOC. 4	A3201	1	2	3	1	7
331 LOC. 5	A3202	5	4	5	3	17
331 LOC. 6	A3203	1	1	1	0	3

Area Monitoring TLD Results for CY 2003^(a) (continued)

TLD Location	TLD ID#	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)
		1st Quarter	2nd Quarter	3rd Quarter	4th Quarter	Annual
331 LOC. 7	A3204	17	22	29	0	68
331 LOC. 8	A3205	2	0	4	2	8
331 LOC. 9	A3206	2	1	2	1	6
331, LOC. 10	A3232	(c)	0	7	4	11
331, LOC. 11	A3237	(c)	(c)	(c)	0	0
331C, LOC. 1	A3207	0	0	(b)	0	0
331D, LOC. 1	A3208	0	0	0	0	0
331H, LOC. 1	A3209	3	3	3	2	11
336-1, LOC. 1	A3073	1	1	4	1	7
337 LOC. 1	A3080	3	4	4	2	13
337 LOC. 2	A3081	3	3	3	3	12
337 LOC. 3	A3082	7	6	7	5	25
337 LOC. 4	A3083	5	3	4	3	15
337 LOC. 5	A3084	4	0	5	4	13
337 LOC. 6	A3085	4	5	4	4	17
338 LOC. 1	A3177	0	0	0	0	0
350 LOC. 1	A3004	0	0	0	0	0
350 LOC. 2	A3005	2	0	0	0	2
622R, LOC. 1	A3086	5	5	7	5	22
622R, LOC. 2	A3087	4	3	3	3	13
747A, LOC. 1	A3088	0	0	0	1	1
747A, Trl LOC. 1	A3089	0	0	0	0	0
2400 LOC. 1	A3113	0	0	0	0	0
2400 LOC. 2	A3114	0	0	0	0	0
2400 LOC. 3	A3115	0	0	3	0	3
2400 LOC. 4	A3116	0	0	0	0	0

Area Monitoring TLD Results for CY 2003^(a) (continued)

TLD Location	TLD ID#	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)
		1st Quarter	2nd Quarter	3rd Quarter	4th Quarter	Annual
3720 LOC. 1	A3047	3	2	3	1	9
3720 LOC. 2	A3048	32	36	35	22	125
3730 LOC. 1	A3049	0	2	3	2	7
3760 LOC. 1	A3009	2	0	2	1	5
3760 LOC. 2	A3010	0	0	1	0	1
APEL LOC. 1	A3217	0	0	0	0	0
APEL LOC. 2	A3228	1	1	1	1	4
BRSW LOC. 1	A3227	3	2	1	4	10
EMSL LOC. 1	A3093	6	3	5	5	19
EMSL LOC. 2	A3094	6 (10) ^e	8 (11) ^e	7	9	29 (21) ^e
EMSL LOC. 3	A3095	6 (19) ^e	5 (23) ^e	6	4 (11) ^e	21 (53) ^e
EMSL LOC. 4	A3096	7	5	5	5	22
EMSL LOC. 5	A3097	6	6	4	5	21
EMSL LOC. 6	A3098	4	3	3	2	12
EMSL LOC. 7	A3211	0	0	0	0	0
EMSL LOC. 8	A3212	1	0	0	0	1
EMSL LOC. 9	A3213	0	0	0	0	0
EMSL LOC. 10	A3214	0	0	0	0	0
EMSL LOC. 11	A3219	0	0	0	0	0
EMSL LOC. 12	A3220	0	0	0	0	0
EMSL LOC. 13	A3223	0	0	0	0	0
EMSL LOC. 14	A3224	0	0	0	0	0
EMSL LOC. 15	A3235	(c)	(c)	(c)	9	9
EMSL LOC. 16	A3236	(c)	(c)	(c)	11	11
ESB LOC. 2	A3092	(b)	0	0	0	0
LSL-II LOC. 1	A3167	5	4	4	4	17

Area Monitoring TLD Results for CY 2003^(a) (continued)

TLD Location	TLD ID#	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)	Deep Dose (mrem)
		1st Quarter	2nd Quarter	3rd Quarter	4th Quarter	Annual
LSL-II LOC. 2	A3168	2	3	2	2	9
LSL-II LOC. 3	A3169	4	4	2	3	13
LSL-II LOC. 4	A3170	2	5	3	2	12
LSL-II LOC. 5	A3171	7	7	7	4	25
LSL-II LOC. 6	A3172	4	5	5	4	18
PSL LOC. 1	A3099	2	1	0	1	4
PSL LOC. 2	A3100	2	1	0	0	3
PSL LOC. 3	A3101	2	4	3	4	13
PSL LOC. 4	A3102	1	(d)	(d)	(d)	1
PSL LOC. 5	A3103	1	3	0	1	5
PSL LOC. 6	A3210	0	(d)	(d)	(d)	0
PSL LOC. 7	A3233	(c)	(c)	0	3	3
PSL LOC. 8	A3238	(c)	(c)	(c)	0	0
PSL LOC 9)	A3234	(c)	(c)	(c)	0	0
RTL LOC. 1	A3105	4	6	6	5	21
RTL LOC. 2	A3106	5	5	5	5	20
RTL LOC. 3	A3107	6	6	4	4	20
RTL LOC. 4	A3108	2	2	3	1	8
RTL LOC. 5	A3109	2	2	4	3	11
RTL LOC. 6	A3110	1	2	3	2	8
Sigma V, LOC. 1	A3186	1	1	1	0	3
Sigma V, LOC. 2	A3187	0	2	1	2	5
Sigma V, LOC. 3	A3188	1	0	0	0	1
Sigma V, LOC. 4	A3189	1	0	(b)	0	1
Sigma V, LOC. 5	A3190	1	1	2	0	4
Sigma V, LOC. 6	A3191	2	1	1	0	4

- (a) - Multiply area TLD result by 0.23 to obtain dose estimates corrected for worker occupancy
- (b) - Area TLD lost
- (c) - Sample location not initiated yet
- (d) - Sample location discontinued
- (e) - Neutron dose from Hanford Standard Dosimeter
- (f) – Neutron dose from Hanford Combination Neutron Dosimeter

Distribution

<u>No. of Copies</u>		<u>No. of Copies</u>
ONSITE		37 Pacific Northwest National Laboratory
3 Fluor Hanford Company		JL Allen J2-40
		JA Armstrong J2-40
RL Hill	L1-08	SR Bivins (5) P8-17
		HJ Black-Kania P7-28
		FJ Bronson J2-40
3 DOE Richland Operations Office		WT Buyers P7-28
		JR Christensen P7-82
TL Aldridge	K8-50	SD Dossett J2-38
R Briggs	K8-50	TD Eaton J2-40
E Parsons	A5-17	RJ Ford J2-40
		RC Free P7-28
		JE Hawkins P7-78
		KE McMullin K8-95
		LA Nelsen J2-40
		CJ Nichols J2-33
		JR Hoyt J2-40
		BA Rathbone P7-02
		PH Rojas P8-95
		RB Sitsler J2-40
		VL Stephens J1-52
		GA Stoetzel (5) J2-40
		Information Release Office (7) K1-06